









Company: Fabtech Australia

Client: Goulburn Valley Water

Application: Replacing a cover on a wastewater treatment

capture and reduce greenhouse

gas emissions, thereby reducing

Location: Shepparton,

basin to improve methane

odor for nearby residents

Benefits: Improves methane

harvesting for conversion into clean energy, reduces carbon footprint, reduces treatment time/

Victoria, Australia



This project supports these UN Sustainability Goals

Shepparton High-Rate Anaerobic Lagoon Cover Replacement



Goulburn Valley Water provides water and wastewater services to more than 60,000 customers covering a region of 20,000 square kilometres. Shepparton is one of Goulburn's 26 wastewater

management facilities and home to the 250ML (mega litres) High-Rate Anaerobic Lagoon treatment basin, which was recently upgraded.

The waste management facility, with a surface area of 50,000m2, converts waste into biogas for conversion into clean energy. The works included removing the existing cover, which had reached the end of its service life, desludging the lagoon, remediating related infrastructure and installing the new cover.



conserves natural resources

INTERNATIONAL
GEOSYNTHETICS
SOCIETY

The International Geosynthetics Society (IGS) is a learned society dedicated to the

scientific and engineering development

of geotextiles, geomembranes, related products, and associated technologies. We

are registered as a non-profit corporation.

costs, improves resident amenity,

To determine the best replacement cover material, Fabtech undertook a rigorous six months of accelerated laboratory testing that concluded a high performance 2mm-thick High-Density Polyethylene (HDPE) would be ideal, providing the client with a 20+ year warranty. The work, which spanned 12 months, began with desludging the existing basin, followed by concrete

band-beam refurbishment and finally fitting the new cover. As the facility was 'live' during installation, a pontoon was floated on the lagoon to help workers lay the cover panels.

Since completion, the new cover has improved methane capture for electricity and reduced the amount of methane released into the atmosphere. It has also helped reduce equivalent CO2 emissions at the plant from 33,000 tonnes to 13,000 tonnes, with further reductions anticipated.

To find out more, contact Fabtech by emailing Russell Hogan at RHogan@fabtech.com.au.

The IGS Sustainability Committee is committed to communicating the positive environmental impact of using geosynthetics, improving worldwide understanding of the sustainability benefits of geosynthetic materials, and supporting the geosynthetics industry maximize the sustainability potential of their projects. For more information, visit our webpage at www.geosyntheticssociety.org/sustainability.

Would you like your product or initiative featured here? Contact IGS Secretariat Manager Elise Oatman at igssec@geosyntheticssociety.org.